

SRS Wiolin Hypoid-Getriebeöl 90



Gear Oil for Drive Axles

February 2019

Characteristics

SRS Wiolin Hypoid-Getriebeöl 90 is blended from selected base oils with carefully adapted additives. Its viscosity is chosen to ensure both no channelling at low temperatures and high lubrication safety at high temperatures.

Application

SRS Wiolin Hypoid-Getriebeöl 90 is intended for very high loaded hypoid meshed axles, bevel and spur gears, steering gears and not synchronized gear boxes in vehicles and machines.

Specifications

- SAE Grade 85W-90
- API GL-5
- MIL-L-2105 C/D

Approvals

- MB-Approval 235.0
- ZF Approval Number ZF000444
ZF TE-ML 16C, 17B, 19B, 21A
- Voith 132.00374400

Recommendations

- Volvo 97310
- MAN 342 Type M1
- Ford SQM-2C-9002 AA
- DAF

SRS Wiolin Hypoid-Getriebeöl 90 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Wiolin Hypoid Getriebeöl 90
SAE Grade	SAE J 306	85W-90
Density at 15°C	DIN 51 757	0.902
Dyn. Viscosity at -26°C	DIN 51 398	-
Dyn. Viscosity at -12°C	DIN 51 398	20,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	198
Kin. Viscosity at 100°C	DIN EN ISO 3104	17.6
Viscosity Index (VI)	DIN ISO 2909	95
Flash Point COC °C	DIN ISO 2592	216
Pour Point	DIN ISO 3016	-24
FZG-Test A/8.3/90	DIN ISO 14635	>12

The above values may vary within the commercial limits.

Made in Germany