

# SRS Antikorrol M plus



## High Performance Monograde Engine Oil

February 2019

### Characteristics

**SRS Antikorrol M plus** is a high performance monograde engine oil with very high corrosion protection properties. A balanced additive package guarantees wear protection and cleanliness in diesel engine operation as well as a high corrosion protection in long shutdown periods.

### Application

Due to its properties **SRS Antikorrol M plus** is particularly suitable for engines subjected to longer times of shutdown periods. SRS Antikorrol M plus is a full load durable engine oil of MTU oil category 2 with additional corrosion protection properties as an anti-corrosion oil for internal conservation.

SRS Antikorrol M plus can also be used for emergency power generators.

**SRS Antikorrol M plus** is approved by the German Army against specification TL 9150-0037/6 with the qualification certificate B-0471.

### Specifications

- Bw-Kode CY6050
- SAE Grade 30
- ACEA E7
- API CI-4

### Approvals

- MTU MTL 5044, Type 2 with special corrosion protection
- MTU MTL 5051, corrosion protection oil for internal conservation
- MTU DDC BR 2000 and 4000
- Bundeswehr: TL 9150-0037/6

SRS Antikorrol M plus is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Antikorrol M plus
SAE Grade		SAE J 300	30
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0.892
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	DIN EN ISO 3104	99.9
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	DIN EN ISO 3104	11.7
Viscosity Index (VI)		DIN ISO 2909	106
Flash Point COC	°C	DIN ISO 2592	245
Pour Point	°C	DIN ISO 3016	- 30
Seawater Immersion Test	Grade	DIN 51 358	0
Total Base Number	mgKOH/g	DIN ISO 3771	10.9

The above values may vary within the commercial limits.

**Made in Germany**

