

SRS Wiolan BF 10



Corrosion Protection Oil

October 2011

Characteristics

SRS Wiolan BF 10 is a spray and corrosion protection oil for spraying onto truck chassis and underbodies, and for the preservation of seasonally operated vehicles such as machines for winter road maintenance and agricultural equipment.

SRS Wiolan BF 10 shows, in addition to the good wet ability resulting from polar active materials, an outstanding capacity to prevent chemical corrosion. Reliable protection against corrosion and rust is offered even under exposure to aggressive atmospheric humidity moisture and salty road waste water. Paints are not attacked.

SRS Wiolan BF 10 is also suitable for the preservation and temporary storage of sheets of metal and semi-finished products over a number of weeks.

SRS Wiolan BF 10 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Wiolan BF 10
Designation	DIN 51 502	R
Colour	DIN ISO 2049	L 1.0
Density at 15°C	g/cm ³ DIN 51 757	0.870
Kin. Viscosity at 20°C	mm ² /s DIN EN ISO 3104	18.5
Kin. Viscosity at 40°C	mm ² /s DIN EN ISO 3104	8.6
Flash Point COC	°C DIN ISO 2592	140
Pour Point	°C DIN ISO 3016	- 15
Steel Corrosion Test	Grade DIN ISO 7120	0-A

The above values may vary within the commercial limits.

Made in Germany