

# SRS Bitaktol KS plus



Fully Synthetic High Performance Two-Stroke Engine Oil

February 2019

## Characteristics

**SRS Bitaktol KS plus** is a fully synthetic high performance self-mixing two-stroke engine oil. The requirements for piston cleanliness, corrosion protection, ring sticking, piston seizure and pre-ignition are fulfilled by far using synthetic components.

## Application

**SRS Bitaktol KS plus** is a low ash engine oil for heavy-duty two-stroke engines (low-smoke). Mixing ratios up to 1:100 according to manufacturer's recommendations are possible.

## Specifications

- ISO L-EGD
- JASO FD
- API TC
- TISI

## Recommendations

- Husqvarna Chainsaw
- Piaggio
- Rotax Snowmobile

SRS Bitaktol KS plus is a product of the H&R ChemPharm GmbH.

Typical Data		Test Method	SRS Bitaktol KS plus
Density at 15°C	g/cm <sup>3</sup>	DIN 51 757	0.894
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	DIN EN ISO 3104	56.9
Kin. Viscosity at 100°C	mm <sup>2</sup> /s	DIN EN ISO 3104	9.02
Viscosity Index (VI)		DIN ISO 2909	137
Flash Point PM	°C	DIN EN ISO 2719	115
Pour Point	°C	DIN ISO 3016	< -42
Base Number	mgKOH/g	DIN ISO 3771	2.0

The above values may vary within the commercial limits.

**Made in Germany**