

SRS Cargolub TFG plus



High Performance Low Friction Engine Oil

Dezember 2020

Characteristics

SRS Cargolub TFG plus is a highly additivated UHPD low friction engine oil for commercial vehicles. Engine manufacturers prefer SAE 10W-40 as year-round grade which is achieved through the use of selected base oils. At low temperature SAE 10W assures excellent cold starting (low cold start wear) and quickest possible oil supply of all engine lubricating points. Extreme conditions are safely controlled by SAE 40 high-temperature viscosity. Friction losses and wear are reduced. The economy is improved through low oil and fuel consumption as well as through higher engine reliability.

Application

SRS Cargolub TFG plus is especially designed for economic supply of exhaust-optimized engines, even under extreme conditions. SRS Cargolub TFG plus assures excellent oxidation and rust protection and stability at high temperatures through the use of special additive systems. High dispersion capacity and piston cleanliness prevent deposits in the engine compartment which may eventually cause a power drop.

SRS Cargolub TFG plus is a year-round high-performance engine oil for use in commercial vehicles, adapted to the EU exhaust standards. It is also in full compliance with all standards for older naturally aspirated and stationary diesel engines.

Specifications

- SAE Grade 10W-40
- ACEA E4/E7
- API CI-4

Approvals

- MAN M 3277
- Scania LDF-2
- MTU MTL 5044 Type 3
- Deutz DQC III-10
- Volvo VDS-3 (STD 417-0002)
- Renault VI RLD-2/RXD
- Mack EO-N / EO-M Plus

Recommendations

- DAF
- MB 228.5
- Cummins CES 20077/20078
- Detroit Diesel 93K215

SRS Cargolub TFG plus is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Cargolub TFG plus
SAE Grade	SAE J 300	10W-40
Density at 15°C	DIN 51 757	0.871
Dyn. Viscosity at -25°C (CCS)	DIN 51 757	5,690
Kin. Viscosity at 40°C	DIN EN ISO 3104	92.1
Kin. Viscosity at 100°C	DIN EN ISO 3104	14.0
Viscosity Index (VI)	DIN ISO 2909	156
Flash Point COC	DIN ISO 2592	232
Pour Point	DIN ISO 3016	-39
Total Base Number	DIN ISO 3771	13.2

The above values may vary within the commercial limits.

Made in Germany

